LPC-P173W-LPx

17.3" Stainless Steel P-cap Panel PC with Intel 7th/6th Gen KabyLake-U/Skylake-U Core™ i7/i5/i3, 6 sides IP66 Waterproof **Feature and Wide Range Power Input**





- York / Desk / Vesa Mounting
- 17.3" P-cap Flat Bezel
- ▶ DC 12~24V Wide Range Power Input
- 1920*1080 Resolution
- ▶ Bottom Side M12 Plastic Connector
- M12 Plastic Waterproof Connectors
- Stainless Steel 316 Food Grade













System	
Processor	7th/6th Gen KabyLake-U/Skylake-U Core™ i7/i5/i3
System Memory	DDR4 2133MHz SO-DIMM, up to 16 GB
External I/O Port	1 x GIGA LAN External Waterproof cables by 1.5 meters (the end side is male RJ45) 1 x USB 2.0 External Waterproof cables by 1.5 meters (the end side is female USB 2.0) 1 x Power External Waterproof cables by 1.5 meters (the end side is 2 wire : ground & +) 1 x COM (1 x RS-232/422/485) External Waterproof cables by 1.5 meters 1 x HDMI (w/o Audio)
Storage	2 x SATA3 (6.0Gb/s) 1 x mSATA (full size mini-PCle)
Operating System	Windows 7 (32/64bit) (Sky Lake-ULT Only)Windows 8.1 (64bit) Windows 10 (64bit)
Expansion	2 x MiniPCle Slot

LCD	
Display Type	17.3" TFT LCD
Max. Resolution	1920*1080
Max. Color	16.7M
Luminance	400nits
View Angle	80/80/60/80
Backlight Lifetime	30,000 hours

Display Type	17.3" TFT LCD	Operating Temp	-20~60 °C , IEC-60068-2-1/2/14
/lax. Resolution	1920*1080	Storage Temp	-20~60 °C
/lax. Color	16.7M	Humidity	10~90% @40 °C, non-condensing
.uminance	400nits	EMC	FCC / CE Class A Certification
/iew Angle	80/80/60/80		CE Class B Compliant
Backlight Lifetime	30,000 hours	Vibration	1.5 Grms @10~500Hz, IEC-60068-2-64

Environment

Power Requirement	
Power Input	M12 Power Input
	DC 12~24V Wide Range
	Power Input

Touch Screen	
Type	17.3" P-cap USB interface

Mechanical	
Construction	Stainless Steel case
IP Rating	IP66 with 6 sides
Mounting	VESA
Dimension	TBC

Ordering Information	
LPC-P173W-LP5	17.3" Stainless Steel P-cap Panel PC with Intel Skylake-U i3-6100U,
	6 sides IP66, and Waterproof M12 Plastic Connector
LPC-P173W-LP6	17.3" Stainless Steel P-cap Panel PC with Intel Skylake-U i5-6300U,
	6 sides IP66, and Waterproof M12 Plastic Connector
LPC-P173W-LPK3	17.3" Stainless Steel P-cap Panel PC with Intel Kabylake-U i3-7100U,
	6 sides IP66, and Waterproof M12 Plastic Connector
LPC-P173W-LPK5	17.3" Stainless Steel P-cap Panel PC with Intel Kabylake-U i5-7300U,
	6 sides IP66, and Waterproof M12 Plastic Connector
WFK-024	WiFi kits w/ cable & Antenna (2.4GHz, 802.11 b/g/n, 1T1R)
WFK-524	WiFi kits w/ cable & Antenna (2.4 & 5GHz, 802.11 a/b/g/n/ac + BT, 2T2R)
04-US-26-00002	120 W / 24V power adapter with 3 pin terminal block (For High Brightness Model)

Ordering Code	
LPC-P173W-LPx Series	-H /-OB/-B/-AG/-AR/-V/-M
H = High Brightness 1000	nits LED backlight
OB = Optical Bonding	
B = Glass Withtout Touch	
AG = Anti-Glare	
AR = Anti-Reflection	
V = Vandal Proof Glass (B	y Project)
M = M12 Metal Connector	

